

TIMBERLINK® GREEN

STAIR TREADS

LOSP Treated Pine Stair Treads



100% Australian Plantation Pine

Stair Treads for the Australian home

For use in outdoor, above ground applications

Stair grooves are compliant to AS 4586 for slip resistance

Saves costs with no need for extra grip tape

TIMBERLINK®
Australia & New Zealand

TIMBERLINK[®] GREEN

Timberlink stair treads are machine graded for structural integrity AND visually graded for good looks, giving them a superior performance and appearance for your stair project.

Application

Timberlink stair treads have been grooved, making them building code compliant when used for domestic purposes. They can be used for a variety of stair case widths and are to be used in conjunction with stair riser kits.

Sizes (mm)	240mm x 45mm
Lengths (mm)	900mm, 1.2m, 1.5m, 1.8m, 2.4m 2.7m & 3.0m (available sizes may differ in some states)



Installation

This product is designed to Australian building code standards. Please check with your local planning requirements to ensure your stair treads are installed correctly.

Finishes

It is strongly recommended that stair treads are stained or painted with a suitable external coating. It is important to note that any coating can affect slip resistance. A non-slip coating is recommended.

Resealing

When cut, notched, drilled or rebated the exposed areas of treated timber should be resealed with a suitable resealing product to ensure a treatment envelope is maintained. We recommend Tanalised[®] Ecoseal, allowing 2 days to dry before final topcoat.

Treatment

All Timberlink Stair treads are treated with H3 LOSP for above ground use.

